



BELT DRIVE 120V


Pressure washer



AVAILABLE UP TO*

1500^{PSI}
3.0GPM

120 volt/15.8 amp



Technical DATA

Available up to 3 GPM - 1500 PSI


- BELT DRIVE - Triplex pump Low RPM
- External adjustable unloader with bypass
- 1.5 to 2 HP Electric motor, TEFC, 1750 RPM, 120V, 1.15 Service factor.
- Powder coated frame, fixed or mobile
- Include: 50 feet 3/8" - 4000 PSI
- Lance 36" and 4 nozzles on quick connect
- Standard pressure washer gun
- Thermal valve 140°F on pump
- 20 feet of extension cord:
 - Nema 5-15P for 13 Amp
 - Nema 5-20P for 15.8 Amp

Available Accessories/Options

- | | |
|--|---------------------------------------|
| ☐ Manual Start and Stop | ☐ Mobile Frame |
| ☐ Hose Reel | ☐ Wall Support |
| ☐ Turbo nozzle | ☐ Foamer |
| ☐ Floor cleaner | |



Foamer



Wall Support

*Product may differ from the picture.
Automatic start/stop shown.

- | | | |
|---------------------------------------|-------------------------------------|--|
| ☐ General Pump | ☐ AR Pump | ☐ Hot Kit 185°F |
| ☐ Udor Pump | ☐ Comet Pump | ☐ Flexible Lance & Nozzle Protector |



BELT DRIVE 120V

Pressure washer

*OPTIONAL

Automatic START & STOP device, to keep your investment in pristine condition.

Reliable electric motor with Totally Enclosed Fan-Cooled (TEFC) system.

Quick-release couplers and tangle-free.

Totally enclosed, compliant, high-impact metal belt guard for operator protection.

High Quality External Unloader with external Bypass for Better durability and performance.

Long lasting low RPM Durable, triplex, oil-bath, high-pressure pump, with three ceramic pistons and forged brass manifold, backed by an industry-leading warranty.

Frame Made with Canadian zinc plated Steel 12 GA for durable and Rust free for years.

*OPTIONAL

Comfortable trigger gun and Ergonomic 36" stainless steel lance wand for operator's comfort.

Rugged chassis made of 1 1/4 inch steel, painted with an epoxy powder coat finish for all-weather resistance.

Vibration-absorbing 13" tubed pneumatic tires with steel wheels for all-terrain maneuvering.

50 feet for high pressure washer hose with 1 wire 3/8" 4000 PSI non marking Hose.

**Product may differ from the picture.
Belt-Drive Automatic start/stop Shown.*

MODEL

PSI

HP

GPM

AMP

PLUG

VOLT

 KW121522S	1200 PSI	1.5 HP	2.2 GPM	13.6 AMP	5-15P	120
 KW1023S	1000 PSI	2.0 HP	3.0 GPM	15.8 AMP	5-20P	120
 KW15222S	1500 PSI	2.0 HP	2.2 GPM	15.8 AMP	5-20P	120