



MEDIUM-DUTY

Pressure washer GAS ENGINE



HOT WATER
330 000 BTU !

4000PSI
4GPM

**Quality
Components**

Technical DATA

Professional quality Honda GX390 engine with electric start drives the pump with commercial grade General triplex pump featuring die-cast body. External unloader provides superior cooling and versatility to further enhance pump life. Direct drive system connects the engine to the pump for a compact and efficient power transfer.

4 GPM - 4000 PSI - 13 HP

- DIRECT DRIVE HOT WATER
- Triplex pump General Pump EZ4040G
- Powder coated steel tube mobile frame
- Included: 50 feet 3/8", + hose guard at both end
- Standard lance 36" with nozzle protector and 4 nozzles on quick connect
- Standard pressure washer gun

Available Accessories

- Foamer
- Hose Reel
- Turbo nozzle
- Floor cleaner



Reliable GX390

*Product may differ from the pictures



KW40134HGP

Pressure washer GAS ENGINE



Honda GX390 electric start w/ 18 amp charge

Triplex direct drive general pump carries a **5 year warranty**

Adjustable thermostat up to 200°F with LED rocker switch and hour/tach meter

7-gallon, removable, rust-proof polyethylene fuel tank with fuel gauge in cap.

13" heavy-duty flat-free tires

Marine sealed battery box with 55 AH AGM deep cycle battery

HEATING COIL. 1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends.

5500 PSI Rated, «Full Sized» 96' length for maximum heat rise and proper heat production.

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame with centre balanced lift hook (above industry standards)

12v DC Oil-fired Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

Comfortable trigger gun and Ergonomic 36" stainless steel lance wand for operator's comfort.

50 feet for high pressure washer hose with 1 wire 3/8" 5000 PSI non marking Hose.

